

Quality Cleaning Products Since 1956

# **Duration**

# Urethane Fortified UHS Finish

#### **Benefits:**

Protects - Extends floor life Durable - Long lasting Clear - No discolouration

# **Description:**

Swish Duration Floor Finish is a special urethane and acrylic polymer combination that enhances both durability and timeless gloss.

#### **Caution:**

- · Adhesion problems may occur with polished ceramics
- · Do not use a previously soiled mop
- · Keep from freezing and out of reach of children
- · Do not use on unsealed wood or cork surfaces
- · Read MSDS completely before using this product

## **Directions & Dilutions:**

# First time application

- 1. Prepare the floor utilizing Swish Liberty or Swish Full Press floor stripper. To completely remove all previously used floor coatings, follow stripping directions.
- 2. Thoroughly rinse and neutralize floor before applying finish.
- 3. Apply 4-6 coats of Swish Duration floor finish with a rayon finish mop or applicator. Allow at least 30 minutes between coats. On porous resilient or stone floors, first seal with 2 coats of Swish Stone & Tile Sealer or apply 2 extra coats of Swish Duration. Let dry thoroughly before buffing or burnishing.

## Recoating

- 1. Dry mop area.
- 2. Clean thoroughly with Swish Sunbeam Neutral Floor Cleaner, rinse and let dry.
- 3. Apply 1-2 new coats of Swish Duration Floor Finish.

#### **Maintenance**

- 1. Dry mop daily.
- 2. Clean with Swish Sunbeam or Swish Winterinse Neutral Floor Cleaner
- 3. Burnish twice a week, or as needed with a UHS burnishing pad.
- 4. Restore gloss once a week with a Swish Restorer. Let dry and burnish with UHS pad.

#### **Product Code & Size:**

#3030-210 210 L #3030-20 20 L #3030-4 4 L

**SWISH CANADA** 

1-800-461-7695 Fax: (705) 745-0220 E-mail: info@swish.ca visit us online at

swishclean.com

SWISH USA

1-800-649-4149 Fax: 1-888-742-7315 E-mail: info@swish.ca