

Duralock

High Traction Floor Finish
Urethane Fortified

Benefits:

- High solids – Reduced labour
- Extra high durability – Longer lasting
- Quick drying – Reduces recoat time

Description:

Swish Duralock is a special polymer combination that enhances gloss, durability and slip resistance. Perfect for gym floors and hallways or any other place where a high coefficient of friction is required.

Caution:

- Adhesion problems may occur with polished ceramics
- Do not use previously soiled mop
- Keep from freezing
- Keep out of reach of children
- Do not use on unsealed wood or cork surfaces
- Read MSDS completely before using this product
- Use as directed

Directions & Dilutions:

First time application

1. Prepare the floor utilizing Swish Liberty or Swish Full Press Floor Stripper. Completely remove all previously used floor coatings, follow stripping directions.
2. Thoroughly rinse and neutralize floor before applying finish.
3. Apply 4 – 6 coats of Swish Duralock High Traction Floor Finish with a Swish finish mop or applicator. Allow at least 30 minutes between coats. On porous resilient or stone floors, first seal with 2 coats of Swish Stone and Tile Sealer or apply 2 extra coats of Swish Duralock.
4. Let dry thoroughly.

Recoating

1. Dry mop area.
2. Scrub thoroughly using a blue pad, with Swish Deep Scrub.
3. Apply 1-2 new coats of Swish Duralock Floor Finish.

Maintenance

1. Dry mop daily.
2. Clean with Swish Sunbeam or Swish Winterinse Neutral Floor Cleaner.

Product Code & Size:

#3080-20 20 L

SWISH CANADA

1-800-461-7695
Fax: (705) 745-0220
E-mail: info@swish.ca

visit us online at

swishclean.com

24-7-365

SWISH USA

1-800-649-4149
Fax: 1-888-742-7315
E-mail: info@swish.ca