



We help you shine.™

FORMULA X-TREME™
ULTRA HIGH PERFORMANCE STRIPPER

549 FORMULA X-TREME™

ULTRA HIGH PERFORMANCE STRIPPER

shine on.

Concentrated, powerful, non-ammoniated formula cuts through heavy build-up and hard to remove water-based seals in record time. Low odor!

Product Packaging*



PROD CODE: 549FS
SIZE: 2.50 US gallons (9.5 liters)
ORDER QTY: 2 per case



PROD CODE: 549FSE
SIZE: 2.64 US gallons (10 liters)
ORDER QTY: 2 per case



PROD CODE: 549MP/E*
SIZE: 1.06 US gallons (4 liters)
ORDER QTY: 4 per case

* E = for export



PROD CODE: 549DTC
SIZE: 0.53 US gallons (2 liters)
ORDER QTY: 4 per case

Our **cold water** formula
that's **effective** and fast acting.

Recommended Floor Surfaces:

Vinyl composition tile ("VCT"), most types of terrazzo, marble and quarry tile.

NOTE: Test floor for color fastness in an inconspicuous area.

Directions for use:



DTC: Product to be used only with the AquapHyll dilution control system. For recommended **1:32 dilution rate** use AquapHyll™ Wall Mount dispenser in bucket setting.

1. Mix Formula X-**Treme** UHP Floor Stripper thoroughly with water until uniform per the following dilution ratios:

Light Stripping:

1:40 (3.2 US oz per gallon or 25 ml per 1 liter cold water).

Medium Stripping:

1:30 (4.3 US oz per gallon or 34 ml per 1 liter cold water).

Heavy Stripping:

1:20 (6.4 US oz per gallon or 50 ml per 1 liter cold water).

2. Apply solution liberally to floor and allow to soak for 5-10 minutes. Do not let floor dry - keep floor wet using additional solution as required.
3. Scrub floor with automatic scrubber or stripping machine. Pick up dirty solution with automatic scrubber or wet vac.
4. Rinse floor twice with neutral cleaner and once with water or use EnviroStar Green™ All Purpose Neutralizer per label instructions.
5. Allow floor to dry thoroughly before applying sealer or coating.

* Special packaging for specific requirements available upon request.

Product Data:

Description	Non-ammoniated, ultra high performance stripper	Viscosity (Brookfield) @ 68°F (20°C)	<20 centipoise	Density ASTM D1475-98 (2008)	8.2 lb/gal @ 68°F 0.98 kg/L @ 20°C
Appearance	Clear liquid	Fragrance	None added	VOC (40 CFR Part 59 Subpart C)	60% (as supplied) 2.8% (1:20)
Flash Point ASTM D56-05 (2010)	144°F (62°C)	Shelf Life ASTM D1791-93 (2008)	2 years	VOC (40 CFR Part 59 Subpart C)	1.90% (1:30) 1.43% (1:40)

MSDS sheets available for download at www.pioneer-eclipse.com

Pioneer Eclipse®

©2011 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA
1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • www.pioneer-eclipse.com