



HIGH TRAFFIC FLOOR FINISH

- A high gloss, wet look floor finish
- Durable
- Easy to clean and maintain
- UL approved for slip resistance

	ES96
APPEARANCE	White emulsion
ODOUR	Mild acrylic
SOLUBILITY	Emulsifiable
RELATIVE DENSITY	N/A
pH-VALUE	8-9
VISCOSITY	Water thin
SHELF LIFE	

SIZES		
ES96	18.9 L (5.0 U.S. gallon)	3.78 L (1.0 U.S. gallon)

BENEFITS

- For day after day super high traffic and high gloss floors
- Durable, stain and black heel mark resistance
- Designed for UHS burnishing system
- Easy to clean, easy to maintain
- UL Approved for slip resistance

DISPOSAL

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

PERSONAL PROTECTION

Please refer to product label and SDS

DIRECTIONS

STRIP AND RECOAT

1. Before application, remove old coatings with ES85 Scrub Free Stripper or ES90 Clean Cut Concentrated Stripper
2. Pick up stripper solution using a mop or wet vacuum
3. Thoroughly rinse floor, let floor dry, then dry mop. No sealer required
4. Apply 3-4 coats of ES96 High Traffic Floor Finish
5. Allow at least 15 minutes after dry to touch between coats

SCRUB AND RECOAT

1. Recoat every 4-8 weeks, or as needed
2. Dry mop area
3. Scrub with a blue or green pad with ES91 Deep Scrub
4. Rinse and let dry, then dry mop
5. Apply 1-2 coats of ES96 High Traffic Floor Finish

CLEANING - RESTORING GLOSS

- Dry mop daily
- Burnish regularly

CLEAN AND SHINE

Automatic Scrubbers

- Dry mop
- Clean with ES84 Neutral Cleaner - use a red pad
- Allow floor to dry - burnish

Mop & Bucket

- Dry mop
- Damp mop with ES84 Neutral Cleaner
- No rinse required
- Allow floor to dry - burnish